


Product highlights

- 50Hz Contrast Plus
- Scavem and LTP2
- Dolby Pro logic surround
- TXT/NEXTVIEW Dualscreen
- NEXTVIEW (type 2)
- 440 pages EasyText teletext (level 2.5)
- Active control
- Improved Graphical User Interface

















WideScreen Television 32PW6615

Product highlights

- 50 Hz Contras Plus, Scavem and LTP2 (sharpness) for a crisp and natural picture.
- Dolby Pro logic surround For lifelike sound experience, including 3D surround and integrated centre speaker
- nexTView Program Guide (type 2) Direct access of program info of selected channel and automatic programming of VCR
- TXT/NexTView DualScreen picture + TXT or picture + NexTView.
- 440 Pages EasyText teletext (level 2.5)

· Active Control


Auto Digital Noise Reduction, Auto Sharpness, Auto Color, Auto contrast and Smart Controls. Automatically offers the best picture setting.

- Improved Graphical User Interface Improved Graphical User Interface Easy menu control of all functions
- Full digital sound processing

Supporting Features


- Blackline-S Ultra Flat picture tube
- Colour Transient Improvement (CTI)
- Viewing modes: 4:3, Movie Expand 14:9 & 16:9 (scroll), Subtitle zoom (scroll), Wide Screen, Super zoom
- EasyTune (auto store, ACI and ATS)
- EasyLink + NexTViewlink
- Low power standby
- 90W music output + 20W surround
- Integrated centre speaker
- Dynamic Bass Enhancement
- 3 Loudspeakers + 2 Surround speakers
- Independent headphone volume control

Super Zoom viewing



without visible distortion

Surround sound modes



Technical specifications

Type: FL8a MG

Picture

- Screen diameter: 32"/82cm
- Visible screen size: 76cm
- Picture tube: Blackline-S Ultra Flat 16:9
- Image stability: 50Hz
- Smart Picture control (5 modes)
 - Soft, Natural, Rich, Multi media, Personal
- Brightness, contrast, tint, sharpness, colour

Sound

- Sound system: 3 speaker HiFi stereo
- Output (total): 90W music output + 20W surround
- NICAM stereo
- Frequency response: 20Hz-15kHz, +1/-3dB (ampl.)
- Loudspeakers:
 - 2 x Main 2x6'
 - 1x centre speaker 2x6"
- Smart Sound control
 - Movie, Speech, Music, Multimedia, Personal
- 5 Band graphic equaliser
- · Surround sound speakerboxes packed by

- Easy menu driven installation and operation. Direct acces menu's and cursor control
- Selection of 18 menu languages
- 100 preselections
- Multi-function RC handset controlling - TV.VCR. Sat. DVD
- On screen status display on programmes and functions (OSD)

- Sleeptimer up to 180 minutes
- Electronic lock for parental control
- Favourite programme selection
- Programme title display (transmitted by TXT)
- On screen menu display:
 - Picture menu, Sound menu, Features menu, Dolby menu, Program list, Set-up menu, Installation menu, Program name giving, Language and country selection
- TXT/NexTView DualScreen
- Dealer message and demo modes
- Dealer Link; wireless communication for installation and service

Reception

- Tuning system: 100 fold PLL
- Colour transmission systems

/05, /19, /12, /58

PAL B/G/I + SECAM B/G/L/L' SECAM D/K

A/V connections:

PAL B/G PAL I (UK only)

SECAM B/G NTSC video play back

Channel selections: 120 channels VHF, UHF, S-Channels,

- Hyperband Frequency range: (47.25-855.25MHz)
- Aerial input: 75 Ohm (Coax)
- VCR preselections: 0: 50-99
- Frequency / Channel selection (Germany, Austria and Benelux only)

Teletext

- EasyText teletext (level 2.5): fast access to preferred pages and subcode page scroll
- Recept. standards: WST / TOP / FLOF
- Page memory: 440 pages A.I. used for
 - Habit watch, preferred page and subcode page lists
 - favorite pages
- Program independent subtitles

Remote Control

RC type: RC 25xx

cursor control

Connections

- Front
 - S-Video in
 - video CVBS-in (cinch)
 - audio L/R-in (cinch) with automatic mono switching
 - headphone iack 3.5mm
- Rear
 - Euro A/V connector
 - (RGB-in; CVBS-in/out) with auto image format detection
 - Euro A/V connector (RGB-in:Y/C-in/out; CVBS-in/out) with WYSIWYR select and image format detection
 - Euro A/V connector (CVBS-in)
 - 2 audio-out (cinch) Constant/Variable level
 - surround sound out (cinch)
 - surround sound out (clickfits 4x)

Miscellaneous Ambient temperature : +5/+45°C

- Mains : AC 220-240V ± 10%
- Power consumption:
- <xxxW: Stand by: 0.3W
- Weight: 33.5kg (excl. packaging)
- Dimensions (wxhxd): (excl. connections) 90 7×55 6×57 0



RC 25xx (drawing not correct at date of printing)

Features and specifications subject to change without notice

Release date : February 2000 Chassis : MG 32PW6332 Predecessor(s) : January 2000 Date of issue





